



## Ovens

### ADVANCE CONCEPT ovens

## GAS ADVANCE CONCEPT CONVECTION OVEN, ACG-201

| <u>DIMENSIONS</u> |    | Article  | Packed   |
|-------------------|----|----------|----------|
| Length            | mm | 929,00   | 1.000,00 |
| Depth             | mm | 964,00   | 1.100,00 |
| Height            | mm | 1.841,00 | 2.000,00 |
| Weigth            | Kg | 333,00   | 366,00   |
| Volumen           | m3 | 1,65     | 2,20     |

### ELECTRICITY

| Electric power | KW |                |
|----------------|----|----------------|
| 230V -1+N      |    | 2,40           |
| 230V - III     |    | 2x1,5+T - 10 A |
| 400V - III+N   |    |                |

### WATER

|                           |  |         |
|---------------------------|--|---------|
| Water consumption (lit/h) |  | 30,00   |
| Pressure (Kg/cm2)         |  | 0,5 - 8 |

### GAS

|             |                    |           |
|-------------|--------------------|-----------|
| Power       | KW                 | 36,00     |
|             | Kcal/h             | 30.960,00 |
| LPG         | Consumption (kg/h) | 2,54      |
|             | Pressure (g/cm2)   | 37,00     |
| Natural Gas | Consumption (m3/h) | 3,28      |
|             | Pressure (g/cm2)   | 18,00     |

### STEAM

Not used

### AIR

Not used

### LEVEL SOUND

(dB) 62,00

### Certificate EQNET- CE

99AR313

### GAS ADVANCE CONCEPT CONVECTION OVEN, ACG-201

Technology made simple :

- Easy to use and simple
- Efficient
- Perfect results

Capacity for 20 1/1-GN trays.

Digital push-button controls and two "Scroll" buttons.

Cooking mode by convection (up to 300°C).

Electronic temperature core probe.

Stainless steel burner with electronic control system with sparking plug ignition.

Frequency modulation for the convection burner.

Humidifier button.

Preheating option.

3 Speeds - 2 power ranges.

Cold-Down chamber cooling system.

"Auto-reverse" system to reverse fan rotation.

Error detection system. "Repair service" mode system.

IPX-5 protection.

Door with double glass and hermetic locking and folding interior glass.

Power intake: 230 V -1+N- 2.4 kW.

Gas heating capacity: 30,960 Kcal/h. (36 kW).

Dimensions: 929 x 964 x 1,841 mm.

| Connections points | X   | Y   | Z     | Diameter | Information                                  |
|--------------------|-----|-----|-------|----------|--|
| ELECTRICITY        | 843 | 835 | 110   |          | Prever Interruptor diferencial               |
| COLD WATER         | 847 | 494 | 110   | 3/4"     | Prever llave de corte en la toma             |
| SOFT COLD WATER    | 847 | 559 | 110   | 3/4"     | Prever llave de corte en la toma             |
| DRAIN              | 395 | 160 | 110   | 1"       |  |
| EXHAUST            | 627 | 279 | 1.877 | 120      |  |
| GAS                | 737 | 518 | 110   | R.3/4"G  | Prever regulador y llave de corte individual |

